



(without protection cap)

(without protection cap)

- Protection level: IP20  
 - Temperature range: -10° C ...+70° C

10	3301241010009	FO Single Mode, 9/125 μm	10000 ± 100
9	3301241009009	FO Single Mode, 9/125 μm	9000 ± 90
8	3301241008009	FO Single Mode, 9/125 μm	8000 ± 80
7	3301241007009	FO Single Mode, 9/125 μm	7000 ± 70
6	3301241006009	FO Single Mode, 9/125 μm	6000 ± 60
5	3301241005009	FO Single Mode, 9/125 μm	5000 ± 50
4	3301241004009	FO Single Mode, 9/125 μm	4000 ± 40
3	3301241003009	FO Single Mode, 9/125 μm	3000 ± 30
2	3301241002009	FO Single Mode, 9/125 μm	2000 ± 20
1	3301241001009	FO Single Mode, 9/125 μm	1000 ± 15
Cont. no.	Part. no.	Type of cable	Dim. a[mm]

	All rights reserved Department EC PD - RO	All Dimensions in mm Original Size DIN A3		Scale 1.5:1	Free size tol.	Ref. Sub.	
		Created by DRAGHICI	Inspected by AVRAM	Standardisation HOFFMANN	Date 2012-08-30	State Final Release	
Title Fiber optic jumper cord						Doc-Key / ECH-Nr. 100197832/UGD/008/A 50000054877	
HARTING Electronics GmbH D-32339 Espelkamp		Type TB	Number 3301241XXX0009			Rev. A	Page 1/1